## **DOOR PROSPECT FORM**

Date: / /

New Con	struction	Remodeling				
Ship Out		Pick Up	Bill to	Client	Builder	
Client:						
Present Address:						
City:			State	:	Zip:	
	1:				7	
5	Instructional					
	Instructions:					
Door Specs		Double Deer	Transom	Sidolighto		
· -				Sidelights		
Total dimension of the UnitWidth xHeight or Rough OpenindWidth xHeight						
Arch type: Full EyerbrowsGothic None Radius or Springline    Finish						
Foot Boards: YesNoIF YES specify height of footboard						
Swing IN OUT when looking at the door from the outside						
Which door should be active on a set of double doors? Right LeftOUT when looking at the door from the outside Hardware location on a single door? Right Left when looking at the door from the outside						
From the builder						
Jam Width :Stud size in a new construction  Total Wall width on a remodel    Finish of the wall on the outside:BrickStone Stucco						
	r clearThickness.					
Hardware Preparation Specs:						
Standard: 2 1/8" boring, 2 3/8" backset, 5 ½" Center to Center Std Single Bore with decorative pull handles from Solara and roller latches. Pull handle model #						
Mortise	e Lock, see our standard r	mortise lock preparati	on specs enclosed			
Floor Level:						
	Standard 1 7/8" or commercial 7/8" (Jam & Door level difference)Type of flooring used: Wood Floors: " wood floor height Marble or stone" marble height					
Notes:	-					

142 Howell St. Dallas, TX 75207 Phone (214) 744-9900 Fax (214) 744-9910

